

Kelowna Forklift Training Course

Kelowna Forklift Training Course - Federal and industry regulators have established the criteria for forklift safety training according to their existing regulations and standards. Individuals wanting to operate a forklift should finish a forklift training program before making use of one of these machinery. The accredited Forklift Operator Training Program is meant to provide trainees with the knowledge and practical skills to become a forklift operator.

There are forklift operation safety rules which must be followed pertaining to pre-shift checks, and regulations for loading and lifting.

Prior to a shift beginning, an inspection checklist must be carried out and given to the Supervisor or Instructor. If any maintenance issue is discovered, the machine must not be operated until the problem is addressed. To indicate the equipment is out of service, the keys must be removed from the ignition and a warning tag placed in a place which is seen.

Safety rules for loading will comprise checking the load rating capacity on the forklift to determine how much the machine could handle. When starting the equipment, the forks should be in the downward position. Remember that there is a loss of around 100 pounds carrying capacity for every inch further away from the carriage that the load is carried.

Lifting must begin with the driver moving to a stopped position roughly three inches away from the load. The mast should then be leveled until it has reached a right angle with the load. Lift the forks to one inch under the slot on the pallet and drive forward. Afterward lift forks four inches. Tilt back the load to secure it for moving. Drive the lift backwards if the load obscures frontal vision. Check behind and honk in order to warn other personnel. Do not allow forks to drag on the ground.

Forklift loads should be loaded in such a way that they are secure and do not create a danger to other people or objects. Restraining loads is required for materials which can shift during transport and destabilize the forklift.

Drums could be strapped together to be able to prevent shifting and movement of the drums. Operators of forklifts should drive slowly when transporting liquids, to decrease instability in the forklift.